



Features

- Up to 16ch - Nodestream Live
- Up to 4ch - Nodestream X
- Passively cooled
- Compact form factor
- Extended operating temperature
- DIN and surface mounting
- Native HDMI input
- Native RS232 serial
- Dual Gigabit LAN
- Low power wide range DC input

Technical Specifications

Channels	Nodestream X	4
	Nodestream Live	16
Physical	Dimensions (H x W x D)	51mm x 110mm x 72.5mm (2" x 4.33" x 2.85")
	Weight	400g (0.88lbs)
Power	Input voltage	12 - 28VDC
	Power consumption	7w (typical)
Environmental	Operating temperature	0 °C to 50 °C / 32 °F to 140 °F
	Humidity	Operating: 0% to 90% (non-condensing)
Certification		RCM, CE, UKCA, FCC
Video	HDMI output	Up to 4K/60
	HDMI input	Up to 1080/60
	USB video source	Uncompressed YUV 4:2:0 / MJPEG
Network Streams	Supported protocols	RTSP/RTP/HTTP/UDP (MPEG,H.264, H.265)
Other Interfaces	USB	Type A 3.0
	Serial	RS232, 3.5mm TRS
	Ethernet	2 x RJ45, 10/100/1000
What's Included	PSU	AC/DC 36w
	Power cable	2pin to 2.5mm barrel @1m
	Serial cable	3.5mm to D9 @1m
	Mounts	Surface & DIN

