



Features

Up to 16ch - Nodestream Live
 Up to 4ch - Nodestream X
 4 x Display outputs
 Optional input cards
 Native RS232 serial
 Dual Gigabit LAN
 Analog audio input/output

Technical Specifications

Channels	Nodestream X	4
	Nodestream Live	16
Physical	Dimensions (H x W x D)	132mm x 482mm x 380mm
	Weight	8.2kg
Power	Input voltage	100 - 240VAC 47/63Hz
	Power consumption	150w (typical)
Environmental	Operating temperature	0 °C to 35 °C
	Humidity	Operating: 0% to 90% (non-condensing)
Certification		RCM, CE, UKCA, FCC
Video	HDMI output	4 x 1080/60
	HDMI input	4 x 1080/60 (optional card required)
	SDI input	4 x 1080/60 (optional card required)
	Composite input	6 x 720/30 (optional card required)
	USB video source	Uncompressed YUV 4:2:0 / MJPEG
Network Streams	Supported protocols	RTSP/RTP/HTTP/UDP (MPEG,H.264, H.265)
Other Interfaces	USB	6 x Type A 3.0
	Serial	RS232, D9
	Ethernet	2 x RJ45, 10/100/1000
What's Included	Power cable	IEC13 (region specific)
	Converter	1 xMini DP to HDMI

